

**DL**

Since 1936

CHEMICALS

Manufacturer of Sealants

The logo for Parasilico features the word "Parasilico" in a bold, white, sans-serif font with a black outline. A green snake graphic is positioned above the letters "i" and "l".

PARA PRODUCT LINE

**PROFESSIONAL QUALITY
HIGH SERVICE
STRONG BRANDS**

Distributed by:-
National Seal Systems Ltd
Unit 210 Holly Road Ph: 01 -4565170
Western Ind. Est. Fax: 01- 4502371
Naas Road, Dublin 12
Email:-info@nationalseal.ie
Web:-www.nationalseal.ie

SILICONE SEALANTS



Neutral curing silicone. Excellent adhesion on glass, treated wood and PVCu, aluminium, ...
Fast curing time. BS 5889 type A.



Neutral silicone sealant. Has been especially formulated for all types of sanitary applications (high humidity areas) BS 5889 type A. Excellent adhesion on plastics without primer.



Neutral alcoxy curing silicone sealant. Can be painted with most wood paints that meet the VOC 2010 regulations.



Neutral curing silicone sealant, suitable for natural stone. Does not cause staining on natural stone. Also suitable for sanitary applications.



Neutral curing silicone sealant. Heat resistant: 250°C (300°C short term). Excellent adhesion on metals and many plastics.



Neutral curing silicone sealant, type alcoxy. Fast curing and excellent adhesion on the majority of building materials.



Neutral curing silicone, especially designed for plastics, such as polyacrylate and polycarbonate.



Neutral alcoxy curing silicone sealant, appropriate for constructions and exterior weather sealing applications such as perimeter joints and joints between glazing and supporting structures.



Neutral silicone sealant, extremely appropriate for tile joints and use in sanitary applications. Thanks to its high viscosity and body, extremely easy to apply and finish.



Sealant compound with permanent elasticity that is applied as a joint in triangular form as windows used to be installed.



Silicone sealant based on an acetoxycuring system. Excellent adhesion on anodised aluminium, glass and metals. BS 5889 type B.



Silicone sealant based on an acetoxycuring system. Has been especially formulated for all types of sanitary applications (high humidity areas) BS 5889 type B.



Acetoxycuring silicone rubber with high mechanical strength. Especially for aquarium construction.



Acetoxycuring silicone sealant, becomes crystal clear after vulcanization. Specially formulated for sealing display cases, glass bricks and lighting domes.



Acetoxycuring silicone sealant. Heat resistant: 250°C (300°C short term).



Acetoxycuring silicone sealant for tiling and all types of sanitary applications. Extremely easy to apply and finish.

POLYURETHANE SEALANTS



Low modulus PU sealant for use on a vast range of all kinds of materials. Maximum movement capacity: 30%.



Low modulus PU sealant with a very long skinforming time (8h). Especially designed for expansion joints between panels and construction of water retaining structures. WRAS approved product.



Medium modulus PU sealant for sealing and bonding in the automotive and truck industry. Also for construction joints in building industry. WRAS approved product.



PU sealant for structural bonding (mechanical fixing not necessary). Very fast curing time. Can be sanded.



P.U. Sealant especially formulated for windscreens. Short skinforming time and fast curing time. Use with primer DL 2001.

PRIMERS



Universal primer for Detaflex and Parabond 600 (if required). Colour: black



Universal primer for Detaflex and Parabond 600 (if required). Colour: transparent



Primer suitable for porous and alkaline surfaces.



Primer for non-porous materials.



Primer in order to obtain an ideal adherence of the parquet adhesives. Also reinforces floor surfaces on a concrete base. Can be used on porous substrates and tiled floors.

MS-POLYMERS & HYBRID SEALANTS



High quality glue based on hybrid polymers with a very fast build-up of internal strength. The glue obtains 75% of its final strength already after 4 hours when gluing porous materials.

Fast curing high modulus adhesive based on MS polymers. Highly suitable for bonding on a vast range of materials.

Crystal clear adhesive sealant based on MS polymers. For all joining work where transparency is necessary.

High modulus adhesive based on MS polymer with exceptional initial adhesive strength (tack).

High quality glue based on MS-polymer with an extremely high and direct first time contact quality. For gluing and assembly of practically all heavy materials on just about every background.

Quick curing and easily sprayable elastic adhesive sealant based on MS polymers. Specially developed for gluing big surfaces. To apply with a special pneumatic sealant gun.

Sealant based on Hybrid polymers with a low Shore A, especially developed for sealing porous materials like AAC blocks.

Medium modulus adhesive sealant based on hybrid polymers, for general application in the building industry.

Medium modulus glazing adhesive sealant, based on hybrid polymers. Perfectly paintable with alkyd paints and water-based systems. High UV-resistance.

Universal parquet adhesive based on hybrid polymers. For all kinds of mosaic parquet and wooden boards (suitable for use with floor heating). Easy to spread.

Universal parquet adhesive based on hybrid polymers. For all kinds of mosaic parquet and wooden boards (suitable for use with floor heating). Dries extremely fast: one can tread on the parquet after curing for 8 hrs.

Super strong, elastic and ready to use hybrid polymer based glue which is extremely strong when dry. Extremely appropriate for vertical, full surface bonding.

Fast curing, flexible adhesive sealant MS-Polymer based. Designed for bonding without primer of several metals, such as zinc, copper and lead.

PLASTIC SEALANT



Paintable acrylic sealant for joints between windows and walls, around doors and windows frames. Appropriate for joints with low movement (max. 12.5%). Also for the filling of cracks.

Acrylic sealant for sealing and filling of small joints and seems with low movement. Quickly paintable and easy to apply. The paint will not crack and remains matt.

Repair product for the filling of cracks, joints and gaps based on acrylate polymers.

High quality, colour specific and solvent-free acrylic sealant, for sealing connecting joints in parquet, laminate floor covering, skirting boards and walls.

Acrylic emulsion sealant for sealing on porous substrates. Can be used indoors and outdoors. Excellent water resistance. Can be painted very quickly.

Acrylic emulsion sealant, having a rough granulated structure, for sealing on porous substrates.

High modulus clear acrylic sealant for internal joints only.

All weather sealant with good adhesion, even damp/wet non porous surfaces, on bitumen and old butyl joints.

Plasto-elastic bituminous, reinforced by fibers, for gluing and reparations on bituminous surfaces.

Plastic polybutene sealant for concealed joints. Also for joints with small movement.

Sealing kit with high temperature resistance (1000°C) after curing. For the permanent repair and sealing of joints in fireplaces, ovens, chimneys.

ADHESIVES IN POTS



Water-resistant white wood adhesive, according to D3 norm, based on polyvinyl acetate.



Water-resistant white wood adhesive, according to D4 norm, based on polyvinyl acetate.



Water-resistant P.U. wood adhesive, according to D4 norm, with filling properties.



Glue based on synthetic resins, for the bonding of rigid PVC (PVC pressure pipes, PVC profiles).



Thick adhesive, ideal for cold sealing and filling joints in PVCu.



Polychloroprene contact adhesive in liquid form for the bonding of laminated surfaces and others.



Polychloroprene contact adhesive in viscous-liquid form for the bonding of laminated surfaces and others. Ideal for vertical gluing without dripping or smudging.



Cyano-acrylate fast curing adhesive.



Alcohol based vinyl adhesive, for gluing lacquered floors and floorboards of any variety of wood on most common building surfaces.



Very strong, 2 component parquet adhesive, based on PU, for gluing all kind of parquet. Mix component A (9kg resin) with component B (1kg hardener).

ADHESIVES IN CARTRIDGES



Thixotropic polyurethane adhesive, waterproof (D4) with normal curing time.



Thixotropic polyurethane adhesive, waterproof (D4) with small foaming effect. Fast curing time.



One component, waterproof (D4) and thixotropic polyurethane adhesive, with minimal foaming. Fast curing time. Easily sandable.



1-component, waterproof and thixotropic polyurethane adhesive with filling capacities. Formulated for bonding aluminium corner joints during the manufacturing of doors and windows.



Polychloroprene panel adhesive for fixing without screws or nails. Same effect as contact adhesive.



Neutral adhesive for the bonding of extruded polystyrene and other materials.



Special elastic adhesive for bonding of mirrors..



Construction adhesive based on synthetic elastomers and solvents, non aggressive towards polystyrene or the silver backing of mirrors. Excellent initial grip, highly water resistant and maintains its elasticity.



Adhesive sealant based on special elastomers, used for flexible bonding of roof tiles.



FIRE-RETARDANT PRODUCTS



Fire retardant silicone sealant tested according to BS476 part 20: 1987; Approved by Efectis and ISIB (Institute for fire safety).



Fire retardant acrylic sealant tested according to BS476 part 20: 1987; Approved by Efectis and ISIB (Institute for fire safety).



Fire retardant foam, for 240 min. tested according to EN 1366-4: 2006 + A1: 2010 by Afiti.



Fire retardant gun foam, for 240 min. tested according to EN1366-4:2006 + A1: 2010 by Afiti.

IMPREGNATING AGENTS



Impregnating agent based on siloxane for combating capillary rising damp.



Impregnating agent based on siloxane for imparting façades water repellent. Helps keeping the original aspect, protects against (environmental) pollution, frost and moss formation.



Silane/siloxane-based injection cream against upwelling ground water in walls.

POLYURETHANE FOAMS



Hand held 1 component P.U. foam for fixing, insulating and filling, etc.



Hand held 1 component P.U. foam that can be used in all positions (even upright). Ideal for places difficult to reach.



Gun grade 1 component P.U. foam.



2 component P.U. foam for fixing. Low expansion after application.



For internal cleaning of the NBS-gun and/or removing uncured P.U.-foam or polyurethane adhesives.



Remover for cured polyurethane foam.



Release agent that prevents the Parafoam can sticking to the adaptor of the NBS gun.



1C and NBS. Foam adhesive for bonding polystyrene insulation panels.



Gun foam that can be used at ambient temperatures from -10°C. Only available on demand and per full pallet.



Hand held assembly foam for bonding, insulation, filling... Contains less than 0,1% free isocyanates, environment friendly.



One-component P.U. gun foam with high elasticity. Perfectly catches all joint movements. Ideal for durable insulation.

CLEANERS



Cleaner to remove non-cured silicone on glass, rigid PVCu and metals. Can also be used to degrease.



Cleaner for materials in rigid white PVCu and other synthetic material. Can also be used on lacquered metals.



Very strong cleaner to remove dirt or grease from rigid PVCu. Cannot be used on lacquered metals and a lot of synthetic substrates.



Cleaner to remove grease from all metals, also lacquered metals.



Cleaner to remove dirt and grease from metals. On lacquered metals a preliminary test must be done.



Cleaning product + activator in order to remove dust and grease from all lacquered metals. This cleaner has to be used when an oxime-based sealant will be applied.



Cleaning wipes for removing non-cured silicone, non-cured foam, oil, fresh paint... from the hands, tools and surfaces.

SEALING TAPE



Round preformed butyl sealing strips. Compatible with other sealants. Roof and panel lap joints. Available in various diameters.



Cold self-adhesive aluminium/butyl watertight flashing band. Compatible with other sealants. Can be used on glass. Excellent adhesion, even when applied at low temperature.



Elastic, airtight foil-fleece combination for window construction (interior) with a self-adhesive affixing strip.



Elastic, vapour diffusion open function membrane for window construction (exterior) with a self-adhesive affixing strip.

MISCELLANEOUS



Methacrylic mortar without styrene for all stress-free anchoring in dry and wet building materials. For massive and hollow materials. Rapid curing.



Detergent, diluted with water, for smoothing the joints. Does not stain. Delivered with spray nozzle.



Lubricant on the basis of a high-quality, translucent silicone.



Dry fast-levelling mortar designed for floors, appropriate for indoor use. By the simple addition of water a self-levelling mortar is obtained.



Bonding primer for DL Egaline in case of layer on layer floor levelling. Also suitable as prior primer and bonding primer on non-absorbing and smooth surfaces.

DL CHEMICALS
Since 1936 Manufacturer of Sealants

National Seal Systems Limited

Unit 210 Holly Road, Western Industrial Estate,
Naas Road, Dublin 12
Ph 00353-1-4563170 Fax: 00353-1-4502371
Email: info@nationalseal.ie web: www.nationalseal.ie