

Window and Door Restrictors

We offer a family of door restrictors which includes versions with a mechanical hold-open facility.

Suitable for inward and outward opening doors, as well as tilt & turn windows, these products are available with either a bichromated mild steel or stainless steel arm as standard.

The restrictor body fits into the full depth eurogroove at the top of the door (typically) or the bottom of a tilt & turn and restricts the opening to 90 degrees or more, depending on where the frame part is fixed.

The hold-open function prevents the sash from blowing closed in normal wind conditions.

The friction can be seamlessly adjusted and the arm can be easily disconnected should it be necessary to open the door fully.

For more details choose from:

"Hold Open 335mm Restrictor" (12mm airgap minimum)

"Hold Open 500mm Restrictor" (12mm airgap minimum)

"Slimline Hold Open 335mm Restrictor" (4mm airgap minimum)

"Slimline Hold Open 500mm Restrictor" (4mm airgap minimum)

A slimline version is available without the "hold open" facility.

"Slimline Restrictor" (4mm airgap minimum)

"Eurogroove fit" Casement Window Restrictor



< "Hold-open"
500mm
Restrictor

"Hold-open"
335mm
Restrictor >



< Slimline
Restrictor

"Eurogroove
Fit"
Casement Window
Restrictor >



< "Hold-open"
Slimline
Restrictor